

## An Algorithm Based on Wavelet Neural Network for Garment Size Selection

Luo Ronglei<sup>\*1</sup>, He Wenjie<sup>2</sup>, Li Chengyi<sup>2</sup>

<sup>1</sup>School of Fashion, Zhejiang Sci-Tech University, Hangzhou, Zhejiang 310018, China

<sup>2</sup> Engineering Research Center of Clothing of Zhejiang Province, Hangzhou, Zhejiang 310018, China  
Tel. 057186843480, fax: 057186843481

\*Corresponding author, e-mail: luoronglei@163.com

### Abstract

*Size fitting problem is a main obstacle to large scale online garment sales. It is difficult for customers to find the fit garments when they couldn't try on. In this paper, we present an algorithm based on wavelet neural network to help customer choosing their clothing specifications automatically. After the reasonable wavelet function is selected, we established the model structure and the initial parameters. The wavelet neural network is trained by the body measures and the result of AHP algorithm after normalization. The new data are used to test the network. As a result, the error from wavelet neural network is smaller, and the prediction accuracy is proved than that from the algorithm based on traditional BP network.*

**Keywords:** Wavelet neural network, wavelet transform, Garment size selection, matching algorithm, Fit garment matching

### 1. Introduction

With the development of shopping online, the status of garment network sales is rising gradually. According to the statistics, 50% returns are because of unfitted problems since customers can't try garments on by online sales [1]. Many researches devote themselves to find a method can keep customer's measurements match with garment size. In garment size selection algorithm, least-square method has been applied on garment size classification for a long time [2]-[4], it can develop the rationality by using weighting method. Yu [5] put forward a garment size selection method by comparing the matching relationship between figures and garment size. Through the comparison between chest, waist, hip width of figures and the ones on garments, define the matching relationship between figures and garment size. He [6] made research on Yu's method, and proposed modified advice. Xu put forward using AHP method to select garment size [7], the method makes size selection into quantification, which is suitable for garment sales online. On the basis of AHP, Ding and Xu also developed a garment size selection method combined immune algorithms and AHP [8], and support that the prediction accuracy of it is higher than using AHP alone. The method from Chen, made use of BP network to process size classification [9], can apply on garment size selection the same. Some garment size matching algorithms are completed in the form of virtual fitting. In this case, garment pattern has been regarded as a pure geometry problem transferred from two dimensions into three dimensions. Structure grid was made on the patterns, and then finite element method is used to calculate the surface curvature of garment models in order to process salient points matching automatically [10]-[11]. Propose a co-evolutionary immune algorithm for the multi-criteria decision making (MCDM) model, and use the model to solve the large scale garment matching problem [12]. The application of neural network on size selection use the measurement points as input and the corresponding garment sizes as output to train the network [13]-[14].

In this paper, we developed the method of garment size matching on the basis of wavelet neural network. It could input new somatic data and actual suitable garment size by trying on in the follow-up step, by means of training reduce the discrepancy between neural network output and actual results.

## 2. Wavelet neural network size matching algorithm

### 2.1. The selection of wavelet function

We choosed several wavelet functions as the basic function of the neural network, including Morlet's wavelet ,which is used to establish wavelet neural network and has been applied on kinds of fields widely. The wavelet function is used as hidden layer nodes of the network. Hidden layer nodes number is 100. The error of mean square( e) for trainings is defined as follow:

$$e = \sqrt{\frac{1}{L-1} \sum_{i=1}^{i=L} (d_i - y_i)^2} \quad (1)$$

In the formula: L is as hidden layer nodes, d is as the ideal results. (This paper results from AHP), y is as neural network output.

After 100 times training, the network error use Littlewood-paley wavelet function can decrease by about 0.35,while the one use Morlet wavelet is about 0.4.Made experiments on Mexican cap wavelet、 Shannon wavelet to process test, the results is still not better than Littlewood-paley. So this paper uses Littlewood-paley wavelet function as basic function of hidden layer.

### 2.2. Confirm hidden layer nodes number

It's very important for wavelet neural network training study to confirm hidden layer nodes number. if the hidden layer nodes number is too little, network will not possess the essential ability of processing data. On the other side, if there are too many nodes, the network complexity will be increase greatly, which will slow down the network learning speed. process. The common approach is cut-and-try, that is, hidden layer nodes number is confirmed by trials. The test starts with a minor node. As the nodes number is increased step by step, the results were compared. We get the test on the selected hidden layer nodes number. The results are showed as below, in which the errors are the data of 100 times trained.

Table 1. Nodes number and Training error

Nodes number	10	20	40	80	120	160
Error	0.30	0.27	0.21	0.10	0.09	0.08
	1	5	7	6	9	0

The results show that, the training error will be getting smaller as the nodes number get bigger within a certain range. We use the number 100 as our hidden layer nodes number considering that the bigger number would lead to the over-fitting of neural network and influence on training speed.

### 2.3. The selection of initial parameters

The selection of initial parameters makes effect on local minimum point and network convergence speed. If initial weight value is not suitable, learning process will get into local minimum point, and might even stop working. In the wavelet neural network, we could use the random value between (0, 1) as the initialization of connection weights between hidden layer and input layer, and the one between output layer and hidden layer, as we used in BP network.

### 2.4. The confirmation of learning rate

Since the selective wavelet function mostly has limited support, the big learning rate might lead the network parameters to be out of suitable scope, and then the output value might be to zero. So the wavelet learning rate should be a positive number as small as possible.

Experiments shows that the big learning rates (i.e. learning rate of connection coefficient  $\mu_1=0.1$ , learning rate of scaling parameters and translation parameters  $\mu_1=0.1$ ) lead

the network fall into local minimum, thus the training failed. While  $\mu_1=0.1$  and  $\mu_2=0.001$  are selected, the training result is better.

Figure 1 shows the establishment process of neural network structure above. Figure 2 shows the neural network training process.

### 3. Simulation

#### 3.1. The selection for training sample set

637 sets of body data is selected from age 18-35, which is measured by BoSS-21 3D body measurement system from Zhejiang Science and Technology University fashion institute. 600 sets of data are applied for neural network training, and other 37 sets are applied for neural network test.

Neural network structure is  $5 \times 100 \times 1$  (input layer: 5 nodes, hidden layer: 100 nodes, output: 1 node). In the training process, 5 critical part measurements (chest, waist, shoulder width, sleeve length, centre back length) are putted on input layer nodes. The ideal results,  $d$ , is got from the output result of algorithm based on AHP. -1 is used to represent small size, and 0 is used to represent middle size, and 1 is used to represent large size, and 2 is used to represent extra large size. Data is normalized to the interval between  $[-1, 1]$  before training.




Figure 1. wavelet neural network model flow chart




Figure 2. Neural network training process

### 3.2. Network training

After about 100 times training, the error does not decrease obviously anymore. The minimal training error value is 0.38, shown as Fig. 3. The recommended size of 37 sets of body data by neural network is shown as Fig. 4, and the accuracy is 95%, compared with trying on person.




Figure 3. Training error of wavelet neural network




Figure 4. wavelet neural network testing

### 3.3. Contrast experiment

When function  $f(x) = \frac{1}{1+e^{-x}}$  is used as neural network hidden layer primary function and other sets are put the same as the wavelet neural network, the recommended result from the BP algorithm is shown as Fig. 5. The training error decreases into 0.4 in the end. The accuracy of 37 sets of data test samples is 89%.




Figure 5. Training error of Back Propagation network




Figure 6. Back Propagation network testing

## 4. Conclusion

The paper extends the application of wavelet neural network to garment size selection field. The training error and prediction accuracy have been developed compared with the algorithm based on traditional BP network. Indeed, there are still some problems need to solve in future. For example, the network may fall into local minimum point, and requests huge data preparing for models training at early times. And the network needs training data as more as possible. If the samples are not enough, training results will not be better as we expect.

### Acknowledgements

The research work was supported by the Program for Zhejiang Leading Team of Science and Technology Innovation No.2011R50004 and Natural Science Foundation of Zhejiang Provincial under Grant No LQ12F02018.

**References**

- [1] Xu Yichao, Ding Yongsheng. Research and application of garment fit assessments. *Journal of Textile Research*. 2007;28(10): 127-130.
- [2] Wang Jianping, Li Yueli, Yu Fang. Digitized categorization for garment size designation based on the approaching principle. *Journal of Textile Research*. 2007; 28(11): 106-110.
- [3] Zhang Heng, Zhang Xin. The type filing for garment size type based on the lot custom-made. *Journal of Donghua University: Natural Edition*. 2009; 35(4): 436-440.
- [4] Xu Jihong, Zhang Xianghui, Zhang Wenbin. Study on the digitalization of filing custom-made garment types and cutting plan. *Journal of Donghua University: Natural Edition*. 2003; 29(1): 37-42.
- [5] Yu Xiaokun, Wang Jianping. The matching principle of bodily form and garment size series and its application in garment electronic commerce. *Journal of Donghua University: Natural Edition*. 2003; 29(1): 43-47.
- [6] He Li. *Study on anthropometry and size recommending of clothing marketing online*. Wu Xi: Jiangnan University. 2008.
- [7] Xu Yi-Chao, Qi Jie, Ding Yong-Sheng. AHP Based Optimal Selection of Garment Sizes for Online Shopping. *Journal of Donghua University*. 2007; 24(2): 222-225.
- [8] Ding Yongsheng, Xu Yichao. Intelligent optimal selection of garment sizes by using immune algorithm and AHP metho. *Journal of The Textile Institute*. 2008; 99(3): 281-286.
- [9] Chen Liwen. *The research & application of data mining model based on neural network theory*. Da Lian: Dalian Maritime University. 2004: 46-57.
- [10] Decaudin Philippe, Julius Dan, Wither Jamie, et al. Virtual Garments: A fully geometric approach for clothing design. *Computer Graphics Forum*. 2006; 25(3): 625-634.
- [11] Magnenat-Thalmann Nadia, Seo Hyewon, Cordier Frederic. Automatic modeling of virtual humans and body clothing. *Journal of Computer Science and Technology*. 2004; 19(5): pp.575-584.
- [12] Dong Yongsheng, Hu Zhi-Hua, Zhang Wenbin. Multi-criteria decision making approach based on immune co-evolutionary algorithm with application to garment matching problem. *Expert Systems with Applications*. 2011; 38(8): 10377-10383
- [13] Dong Miao, Hao Kuangrong, Ding Yiongsheng. Expert system for size recommending of clothing based on fuzzy neural network. *Microcomputer Applications*. 2010; 26(3): 21-23.
- [14] Zheng Aihua. *Study on size recommending of clothing system based on back propagation neural network*. Hang Zhou: Zhejiang Sci-Tech University.2010.
- [15] Hu Jueliang, Dong Jianming, et al. Garment pattern design based on artificial neural network. *Journal of Textile Research*. 2006; 7(2): 49-52.